

## Dual Bands of Substrate Integrated Waveguide Antennas for 5G Applications

Sarah Majid Hameed<sup>a</sup>, Fadhel Abd ALzahra<sup>b</sup>, Faris Mohammed Ali<sup>c</sup>

<sup>a,b</sup>Department of Physics, Girls College of Education, University of Kufa, Al-Najaf, Iraq.

<sup>c</sup>Department of Communication Technical Engineering, Technical Engineering College\Najaf, AlFurat Al-AI-Awsat Technical University, Al-Najaf, Iraq

**Article History:** Received: 11 January 2021; Revised: 12 February 2021; Accepted: 27 March 2021; Published online: 28 April 2021

**Abstract:** For K-band applications, this article presents a dual band circular slot fixed on a substrate integrated waveguide (SIW) antenna. The simulation result of the antenna includes of a micro strip probe with two rounded slots put in on the top of the radiation plane and located one on top of another for increased bandwidth. This probe was intended with a “dielectric constant” of 2.2 as well as a thickness of 1.5 mm on a Roger layer. Better antenna vibrates at 23.43 GHZ and 30.16 GHZ with a fractional bandwidth of 2.9 GHZ and 1.1 GHZ, consequently. The peak gain attained is about (6.63 and 6.09 dB) above the working frequencies, united. This makes it perfect for K and Ka applications with strong corresponding and returns loss features. The analysis and construction assessment of the proposed probe was led by the EM simulator, CST Microwave Studio

**Keywords:** dual bands, Micro-strip, substrate integrated waveguide SIW, K and Ka –band.

### 1. Introduction


By way of the first 1G network development, cellular networks have grown exponentially since 1980. Up now, broadband networks have achieved the level of a 5G network built to meet the specifications of telecommunications standards such as LTE-Advanced Requirements and IEEE 802.16 m. [1]. Broadband networks and cell phones can be seen everywhere today. The speed of data delivery in digital networking has raised the need for wireless networks. Consequently, the major issues for engineers to design future wireless networks are the rising need for higher connectivity speeds and an increasing users' number. For instance, in the case of wireless communication, uncompressed high-definition video and images demand a very high data transmission rate (more than 1 Gbps).

That this next generation of microwave guidance components often used Microwave Integrated Circuits are published transmission lines (MICs). The advantage of the (MICs) are low-profile systems, however the downside is the lack of high transport capacity and the high Q factor of the traditional waveguides. SICs have been constructed to fix these issues between (MIC) structures and standard waveguides which have the small planar structures advantage like MIC structures with high load capacity and high Q factor, along with waveguides. [3]. One of the techniques of SIC is the optimized waveguide substrate (SIW). Microwave modules, including antennas, active circuits and passive parts, have been very well implemented to SIW technology [4]. The feasibility of the definition for microstrip transformations has been shown in [5]. Coplanar waveguide transformation, also developed in [6][7], Basic waveguide filter and slot antennas were presented in [8],[9],[10]. The lack of radiation caused between the vias was defined in [11]. Inserting a rectangular waveguide through a micro-strip substrate lowers the Q-factor waveguide due to reduced volume and dielectric loading. [6]. SIW suggested a successful finding when it was included in the antenna structure as we can see next.

In this article, the substrate integrated waveguide (SIW) model was developed to the conservative micro-strip to create circular SIW distributions and three circular slots are formed on the upper metallic substrate of the antenna.

### 2. Microstrip Design Procedure

The measurements of the micro-strip reinforcement probe as shown in Fig.1. They are determined by taking into account the patch size and thickness [12].



**Fig. (1)** General configuration of the micro-strip area

Where:

$$w_p = \frac{c}{2f_0\sqrt{\frac{(\epsilon_r + 1)}{2}}} \quad (1)$$

$$L_p = L - 2\Delta L \quad (2)$$

Where:

$$L = \frac{c}{2f_0\sqrt{\epsilon_{reff}}} \quad (3)$$

C: The speed of light in free space.

f<sub>0</sub>: Frequency resonates.

ε<sub>r</sub> : The substrate dielectric constant.

ε<sub>reff</sub> : The effective permeability.

ΔL: duration of the expanded incremental patch.

The effective dielectric constant can be determined as:


$$\epsilon_{reff} = \frac{\epsilon_r + 1}{2} + \frac{\epsilon_r - 1}{2} + \left[1 + 12 \frac{h}{wp}\right]^{\frac{1}{2}} \quad (4)$$

h: Dielectric substrate thickness.

Wp: the patch width;

### 3. SIW Configuration And Design Procedure

The substrate integrated waveguide antenna (SIW) can be signified by metallic rods rows that are inserted between two metallic plates into the dielectric substrate and excited with inset feed as shown in Fig.2.



**Fig.2** The substrate integrated waveguide (SIW) antenna [15].

In frequently to secure a low leakage between the vias gap ( $d < \lambda_g/5$ ) and ( $p \leq 2d$ ) the p (pitch: distance between the two vias) and d (diameter of the hole) and the  $\lambda_g$  (waveguide length) were investigated [14]. The SIW was performed to allow minimized leakage between the vias by using these parameters. [13]. In the configuration of the SIW antenna, two essential parameters must be estimated (equivalent width  $a_{eq}$ ) and (equivalent length  $l_{eff}$ ) as in the following equations:

$$a_{eq} = a_{siw} - \frac{d^2}{0.95 p} \quad (5)$$

$$l_{eff} = l_{siw} - \frac{d^2}{0.95 p} \quad (6)$$

Where

$a_{siw}$ : Width between two rows of vias.

$l_{siw}$  : Length between two rows of vias.

### 3.1 PROPOSED ANTENNA CONFIGURATION

The first recommended antenna was built without (SIW) antenna which can be seen in Fig. (3). Measuring and comparing the findings. The simulation results prove that it has a single band with a resonant frequency of 25.81 GHz and a bandwidth of 0.8 GHz and a return loss of (-13.6 dB) as shown in Fig. (4).




Fig. (3) designed antenna without (SIW)

The s11 the parameter shown in the following figure




Fig. (4): S11 Parameter of the planned antenna without SIW.

The planned SIW antenna structure with a whole measurement (15 mm x 20 mm) was demonstrated on the Roger substrate as a single row with a relative allow ability of = 2.2, a loss of  $\Delta = 0.0013$  and a thickness of  $h = 1.5$  mm. The diameter of the metallic via is fixed at 0.6mm and the pitch between the two vias is 1.2mm. In Fig (5), the geometry of planned SIW antenna is shown. The total measurements of the antenna are listed in the table (1).




Fig. 5 The geometry of planned SIW antenna


Table (1) Antenna Dimensions Of Proposed Model

Symbol	Value	Description
W	15	Total width
L	20	Total length
P	1.2	Pitch between vias
D	0.6	Via diameter

<b>Lf</b>	5	Length of microstrip feed
<b>Wf</b>	1	Width of microstrip_feed
<b>Wp</b>	15	Patch width
<b>Lp</b>	15	Patch length
<b>h</b>	1.5	Thickness of substrate
<b>S1</b>	1	Width of slot 1
<b>S2</b>	0.5	Width of slot 2
<b>S3</b>	0.4	Width of slot 3


**4. RESULTS AND DISCUSSION**

The Coefficient Reflection consequence (S11) response was shown in Fig. (6). The antenna has dual-band resonant activity at 23.43 GHz and 30.16 GHz bandwidth (2.9 GHz) for the lower band, and 1.1 GHz for the upper band for return losses-40.0 dB and-17.49 dB accordingly. This indicates that the new SIW antenna acceptable for the 5G mobile connectivity requirement, radar and satellite systems.



**Fig. (6):** The S11 parameter of the SIW antenna.

As shown in fig. (7). Below, the directivity of the first resonant frequency is (7.1 dB and 6.99 dBi).



**fig. (7)** The directivity

The resonant frequency gain 23.43 GHz and 30.16 GHz is (6.63 dB and 6.09 dB), receptivity. As shown in fig. (8)




Fig. (8) The gain

Table (2) : Characteristic parameters of proposed model (SIW)

Resonance Frequency (GHz)	Return Loss (dB)	Gain (dB)	Directivity (dBi)	Bandwidth (GHz)	Efficiency (%)
43.23	-40.0	6.63	7.1	2.9	93.3
30.16	-17.49	6.09	6.99	1.1	87.12

Again from above SIW technology, the probe effectiveness is improved during the matching time and this leads to bigger directivity and gain so as to make the antenna appropriate for K-band and Ka-band implementations. The actual distribution of the slot antenna at two frequencies is shown in fig. (9) below:




Fig. (9): (a) current distributions at F=23.43 GHz. (b) current distributions at F=30.16 GHz.

## 5. Conclusion

In recent years, multimedia connectivity has practiced a great deal of transition, in other words, the tremendous growth of the mobile device sector, which has contributed to the requirement to offer broadband for these networks. But the spectrum available has become saturated, and this involves an extension of the spectra band and a decrease of its duration. In comparison, the increase in probe gain and presentation is compensated by a greater loss of spread at high frequencies, which means that the obtained signal frequency has to be higher. In this article, a rounded hole patch antenna is gained depended on the SIW structure and introduced as a substitute for dual-band K-band and Ka-band applications. The result displays that the planned antenna shows the ability to include the SIW technique to the model antenna, which will increase the performance on a feasible alternative. The consequence of this antenna meets the principles for 5G mobile connectivity, radar and satellite networks

## References

1. T. S. Rappaport et al, "Millimeter Wave Mobile Communications for 5G Cellular: It Will Work!," in IEEE Access, vol. 1, pp. 335– 349, 2013.
  - A. Ghosh, et al , "Millimeter-Wave Enhanced Local Area Systems: A High-Data-Rate Approach for Future Wireless Networks," in IEEE Journal on Selected Areas in Communications, vol. 32, no. 6, pp. 1152–1163, June 2014.
2. K.WU et al. "Substrate integrated circuits – A new concept for high frequency electronics & optoelectronics". Proc.6th Int.Telecomm. Modern satellite, Cable, broadcast services Conf., 2003. pp 03-10.
3. SRIVASTAVA et al. ," Substrate Integrated Waveguide (NFSIW) for Frequency Selective Applications". RE Journal of Communications Antenna and Propagation (IRECAP),. pp. 259- 263,2012.
4. DESLANDES, D. "Design equations for tapered microstrip-to- substrate integrated waveguide transitions". Microwave Symposium Digest (MTT),. IEEE MTT-S International, 2010. IEEE, 704-707.,2010.
5. DESLANDES, D et al., "Integrated microstrip and rectangular waveguide in planar form. Microwave and Wireless Components Letters. IEEE, 11, 68-70. ", 2001.
6. DESLANDES, D. et al., "Accurate modeling, wave mechanisms, and design considerations of a substrate integrated waveguide". Microwave Theory and Techniques,. IEEE Transactions on, 54, 2516-2526 , 2006.
  - A. M. Hamzah et al., "H-Shaped Fractal Slots Based Highly Miniaturized Substrate Integrated Waveguide Metamaterial Bandpass Filters for C-Band Applications," vol. 86, no. March, pp. 139–158, 2020.
7. L. Yan et al., "Simulation and experiment on SIW slot array antennas," IEEE Microw. Wirel. Components Lett, pp. 446–448, Sep. 2004, doi: 10.1109/LMWC.2004.832081 , .., vol. 14, no. 9,2004.
8. S. Mukherjee et al., "Broadband substrate integrated waveguide cavity-backed bow-tie slot antenna," IEEE Antennas Wirel. Propag. Lett., , doi: 10.1109/LAWP.2014.2330743, vol. 13, no. c, pp. 1152–1155, 2014.
9. SAMAH et al., "Study of design consideration and performance analysis of substrate integrated waveguide components". Degree of Master,. Universiti Teknikal Malaysia, Melaka, 2011.
10. Balanis et al., "ANTENNA THEORY ANALYSIS AND DESIGN ",1938, "Modern antenna hand book / Constantine A. Balanis. , Published by John Wiley & Sons, Inc., Hoboken, New Jersey., 4th ed,2016.
11. T. Djera et al., "Handbook of Antenna Technologies", no. Salmon 2004. 2014.
12. K. Wu et al, "The substrate integrated circuits-A new concept for high-frequency electronics and optoelectronics," 6th Int. Conf. Telecommun. Mod. Satell. Cable Broadcast. Serv. TELSIS 2003 Proc, doi: 10.1109/TELSIS.2003.1246173, vol. 1, 2003.
13. Hadi R. Muwafaq et al., " Dual Bands Microstrip Substrate Integrated Waveguide (SIW) Antenna for K-band Applications " , ATU-FJIECE – Volume: 01 – March 30, 2020, © FJIECE. P: 2. 2020